AURORA®
LIGHTING

Product Description: MR16 Fire Rated Downlight

Integrated intumescent material completely seals the downlight and cut-out in the event of a fire. The A2-DLL681 features reduced recess depth for shallow ceiling voids and is intended for use with aluminium reflector lamps only. Registered Community Design 390612-0001/2/3 and UK Patent GB2426321.

SKU Code	Beam Angle	Finish Colour
A2-DLL681PC	36	Polished Chrome
A2-DLL681SN	36	Satin Nickel
A2-DLL681W	36	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Requires a suitable 12V Constant Voltage Transformer (Not Included)
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- UK Patent GB2426321

Product Specs:

Input Voltage	12~12V AC	Lifetime L70 (hrs)	3000hrs
Lamp Base	GU5.3	Overall Diameter (mm)	85
Weight (Kg)	0.223	Cutout Diameter (mm)	72-

Compliance & Approvals:

Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.