



Product Description:

T8 IP65 Non-Corrosive Fluorescent

SKU Code	Wattage	Colour	Lumens
AU-ANT214	28	4000	1200
AU-ANT214SS	28	4000	
Line Drawing	Polar Curve	Colo	ur
Feature & Benefits			
<ul> <li>IP65 Mains voltage 2x14W T5 polycarbonate non-corrosive fitting</li> <li>Suitable for car parks, sports stadiums, boiler rooms, factories, farm buildings etc</li> <li>Impact resistant polycarbonate body and diffuser</li> </ul>	<ul> <li>Integral high frequency electronic ballast(s)</li> <li>Supplied with lockable polycarbonate diffuser clips (stainless steel clips available separately - AU-ANTSSC - see table below for quantity for each fitting)</li> </ul>	<ul> <li>Hinged gear tray for ease of installation</li> <li>20mm conduit entries</li> </ul>	<ul> <li>Supplied with stainless steel fixing brackets and cable glands</li> <li>Lamp included</li> </ul>

## Product Specs:

Input Voltage	220~250V AC	IP Rating	IP65
Width (mm)	100	Length (mm)	605
Weight (Kg)	1.166	Height (mm)	100

Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.