

Product Description: 15W IP65 Bulkhead

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-BH103A	15	4000	1100	74	120	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 Polycarbonate LED Bulkhead
- 3 Hour maintained emergency back-up option (AU-BH103AEM) and microwave sensor option (AU-BH103AMS) available
- 5m detection range on microwave sensor
- 30 degrees - 150 degrees detection angle on microwave sensor
- 400W maximum load on microwave sensor
- Microwave sensor uses 0.6W in standby mode, 1.2W in operation
- Detection area on microwave sensor can be adjusted from 10%-100%
- Hold time on microwave sensor can be adjusted from 5 seconds - 25 minutes
- Daylight threshold on microwave sensor can be adjusted from 2 lux - 500 lux
- Not affected by frequent switching e.g. when used with occupancy controls
- Tough polycarbonate body for vandal resistance
- Opal diffuser
- Supplied with White and Polished Chrome trims
- Wall or ceiling mounting
- 20mm conduit entries
- Non-dimmable
- (L70) at a 25,000 hour lifetime
- 3 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	240~240V AC
Lifetime L70 (hrs)	50000hrs
Projection (mm)	108

IP Rating	IP65
Overall Diameter (mm)	326
Height (mm)	108

Compliance & Approvals:

Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.