

Product Description: 15W IP65 Emergency Bulkhead

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-BH104AEM	15	4000	1100	74	120	White
AU-BH104AEMBO	15	4000	1100	74	120	Black
AU-BH104AEMBP	15	4000	1100	74	120	Black
AU-BH104AEMWO	15	4000	1100	74	120	White
AU-BH104AEMWP	15	4000	1100	74	120	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 Polycarbonate LED bulkhead
- 3 Hour maintained emergency back-up option (AU-BH104AEM) and microwave sensor option (AU-BH104AMS) available
- Life not affected by frequent switching e.g. when used with occupancy controls
- Tough polycarbonate body for vandal resistance
- Opal diffuser
- Wall or ceiling mounting
- 20mm conduit entries
- Emergency version has integral 3 hour battery back-up
- Non-dimmable
- Life to 70% lumen maintenance (L70) - 25,000 hours
- 3 Year Warranty - *see www.auroralighting.com for details

Product Specs:

Input Voltage	240~240V AC	IP Rating	IP65
Lifetime L70 (hrs)	25000hrs	Overall Diameter (mm)	280
Projection (mm)	83	Height (mm)	83

Compliance & Approvals:

Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.