



Product Description:

15W IP65 Square Microwave Sensor Bulkhead

| SKU Code     | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|--------------|---------|--------|--------|-------------|------------|---------------|
| AU-BH105MSB0 | 15      | 4000   | 850    | 57          | 120        | Black         |
| AU-BH105MSBP | 15      | 4000   | 1100   |             | 120        | Black         |
| AU-BH105MSW0 | 15      | 4000   | 850    | 57          | 120        | White         |
| AU-BH105MSWP | 15      | 4000   | 1100   |             | 120        | White         |

Line Drawing Polar Curve Colour

## Feature & Benefits

- IP65 Polycarbonate LED Bulkhead
- 3 Hour maintained emergency back-up option (AU-BH104EM, AU-BH105EM)
- Microwave sensor option (AU-BH104MS, AU-BH105MS) available
- Customisable 5m detection range on microwave sensor. 30 degrees - 150 degrees detection angle
- 400W maximum load on microwave sensor

- Microwave sensor uses 0.6W in
  Opal diffuser standby mode, 1.2W in operation
- Hold time on microwave sensor can be adjusted from 5 seconds 25 minutes
- Life not affected by frequent switching e.g. when used with occupancy controls
- Tough polycarbonate body for vandal resistance

- Supplied with white and polished chrome trims
- Wall or ceiling mounting
- 20mm conduit entries
- Emergency version has integral 3 hour battery back-up
- Non-dimmable
- Life to 70% lumen maintenance (L70) - 25,000 hours
- 3 Years Warranty \*see www.auroralighting.com for details

## **Product Specs:**

| Input Voltage      | 240~240V AC | IP Rating   | IP65  |
|--------------------|-------------|-------------|-------|
| Lifetime L70 (hrs) | 50000hrs    | Width (mm)  | 245   |
| Length (mm)        | 245         | Weight (Kg) | 0.985 |
| Projection (mm)    | 83          | Height (mm) | 83    |
|                    |             |             |       |

## Compliance & Approvals:













This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.