

Product Description: dSeries™ 32W IP44 Dimmable Downlight

Range of dSeries™ fixed, dimmable IP44 LED downlights fitted with icDOB™ (Driver on board) for maximum reliability and lifetime. No separate driver required. CrystalCool™ next generation thermal management. Available in 13W, 19W and 32W. Suitable for cut-out of 90mm, 150mm and 210mm. Available in 3000K and 4000K. Emergency and Baffled versions available. Smooth and linear dimming on most leading and trailing edge dimmers. Supplied with White bezel.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-DL10032BW/30	32	3000	2100	66	120	White	Dimmable
AU-DL10032BW/30EM	32	3000	2100	66	120	White	Emergency
AU-DL10032BW/40	32	4000	2250	71	120	White	Dimmable
AU-DL10032BW/40EM	32	4000	2250	71	120	White	Emergency
AU-DLB10032BW/30	32	3000	2100	66	120	White	Non Dimmable
AU-DLB10032BW/30EM	32	3000	2100	66	120	White	Emergency
AU-DLB10032BW/40	32	4000	2250	71	120	White	Non Dimmable
AU-DLB10032BW/40EM	32	4000	2250	71	120	White	Emergency

Line Drawing

Polar Curve

Colour

Feature & Benefits

- icDOB™ (Driver on Board) for maximum reliability and lifetime - NO SEPARATE DRIVER REQUIRED
- CrystalCool™ next generation thermal management offers brighter light for longer
- Reduced heatsink due to CrystalCool™ Technology allows installation in shallow ceiling voids
- IP44 Rated
- Lightweight polycarbonate bezel
- Range of sizes and lumens outputs
- Smooth and linear dimming on most leading / trailing edge dimmers
- Baffle and Emergency options available
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	40000hrs
Weight (Kg)	0.900
Product Type	Downlights
Operating Temp. (Max) °C	25°C

Input Frequency	50/60HZ
IP Rating	IP44
Overall Diameter (mm)	230
Height (mm)	83
Cutout Diameter (mm)	210-210

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.