

Product Description: GX10 Adjustable Fire Rated Downlight

SKU Code	Colour	Lumens
AU-DLH922PC	3000	2940
AU-DLH922SN	3000	2940
AU-DLH922W	3000	2940

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Registered Community Design 390612-0001/2/3
- UK Patent GB2426321
- Suitable for use with Sylvania Britespot or GE CMH PAR16 HID lamps
- This luminaire requires a TD-SH35Z HID Ballast (not included)
- 84 Lumens per Watt allows compliance with the Building Regulations Approved document L2A/B requiring the use of energy efficient luminaires in commercial buildings
- High output, energy efficient, compact metal-halide reflector lamp for general lighting
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Range of designer accessories available to customise your installation & create varied lighting effects
- Non-Dimmable
- 2 Year guarantee

## Product Specs:

Overall Diameter (mm)	95	Weight (Kg)	0.337
Height (mm)	147	Cutout Diameter (mm)	85-

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.