

Product Description:

MR16 Adjustable Baffle Fire Rated Downlight

This is a Dimmable 12V MR11 Aluminium Adjustable Recessed Baffle Fire Rated Downlight. This lamp reduces direct glare. It is fitted with intumescent material which completely seals the downlight and cut-out in the event of a fire. Suitable for 30, 60 & 90 minute fire rated ceilings.

SKU Code		Beam Angle	Finish Colour
AU-DLL472MWB		36	Matt White
Line Drawing	Polar Curve	Col	our
Feature & Benefits			
 Integrated intumescent material completely seals the downlight and cut-out in the event of a fire Tested in 30, 60 & 90 minute fire rated ceilings Recessed lamp reduces direct glare 	 Lock ring for ease of lamp replacement Requires a suitable 12V Constant Voltage Transformer (Not Included) Tested to BS476 Part 21 	 Tested to BS EN ISO 140- 3:1995 & BS EN ISO 140- 6:1998 (Acoustics) confirming that they maintain the ability f an internal or separating floor to provide sound insulation These products are available i a Matt White finish with Black baffle only 	or details

Product Specs:

Input Voltage	12~12V AC	Lifetime L70 (hrs)	3000hrs
Lamp Base	GU4.0	Overall Diameter (mm)	80
Weight (Kg)	0.227	Height (mm)	115
Cutout Diameter (mm)	65-		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.