

Product Description: MR11 Fixed Fire Rated Downlight

SKU Code	Finish Colour
AU-DLL691PB	Polished Brass
AU-DLL691PC	Polished Chrome
AU-DLL691SN	Satin Nickel
AU-DLL691SS	Satin Silver
AU-DLL691W	White

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Registered Community Design 915509-0001/2/3
- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Suitable for use with AU-MR113 3W 35mm LED lamp
- Lamp not included
- 3 Year Warranty - see [www.auroralighting.com](http://www.auroralighting.com) for details

## Product Specs:

Input Voltage	12~12V AC	IP Rating	IP20
Lifetime L70 (hrs)	3000hrs	Lamp Base	GU4.0
Overall Diameter (mm)	64	Weight (Kg)	0.172
Height (mm)	115	Cutout Diameter (mm)	50-

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.