

Product Description: MR16 Fixed Fire Rated Downlight

Superb basic MR16 Fire rated fixed downlight. This fitting is rated to withstand up to 90 minutes in a real fire without breaking the safety barrier. It looks great once installed and has a cutout diameter of 75 mm.

SKU Code	Beam Angle	Finish Colour
AU-DLL991MW	36	Matt White
AU-DLL991PB	36	Polished Brass
AU-DLL991PC	36	Polished Chrome
AU-DLL991SN	36	Satin Nickel
AU-DLL991SS	36	Satin Silver
AU-DLL991W	36	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Requires a suitable 12V Constant Voltage Transformer (Not Included)
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- UK Patent GB2426321
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation

Product Specs:

Input Voltage	12~12V AC	Lifetime L70 (hrs)	3000hrs
Lamp Base	GU5.3	Overall Diameter (mm)	85
Weight (Kg)	0.252	Height (mm)	139
Cutout Diameter (mm)	75-		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.