

Product Description:

SGU10 Fixed Fire Rated Downlight

The AU-DLM641 is a PAR20 lamp sized fixed fitting with a cutout diameter of 90mm. It is fire rated and can be covered by insulation material too. It takes a PAR20 lamp which can be CFL or LED. We recommend the AU-GUF4011 range of bulbs but others will fit also. Will not fit a standard GU10 lamp.

SKU Code	Finish Colour
AU-DLM641PC	Polished Chrome
AU-DLM641SN	Satin Nickel
AU-DLM641W	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Integrated heat sink allows downlights to be covered with thermal insulation. Downlight insulation guard not required
- 45 Lumens per Watt output allows compliance with the Building Regulations Approved document L1A/B requiring the use of energy efficient luminaires in dwellings
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Registered Community Design 000349725-0002/3 (fitting)
- Tested to BS476 Part 21

Product Specs:

Input Voltage	220~240V AC	Lamp Base	GU10
Overall Diameter (mm)	101	Weight (Kg)	0.360
Height (mm)	141	Cutout Diameter (mm)	90-

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.