



Product Description:

T8 10W Frosted Emergency

| SKU Code        | Colour | Lumens | Lumens/Watt | Wattage |
|-----------------|--------|--------|-------------|---------|
| AU-EM86010FR/40 | 4000   | 785    | 79          | 10      |
| AU-EM86010FR/64 | 6400   | 800    | 80          | 10      |

Line Drawing Polar Curve Colour

## Feature & Benefits

- Community Registered Design 001909185
- International Patent W02013008030
- UK Patent GB2488845A
- Supplied with remote battery pack for ease of maintenance
- >10% lumen output in emergency operation
- Rotatable end caps
- 3 Rows of SMD LEDs
- High colour rendering index (Ra) 80
- Aluminium back for heatsinking of LEDs
- Impact resistant frosted polycarbonate diffuser
- High power factor >0.90
- Suitable for use at -20° to +40°C
- 1kV surge protection
- Beam 120°
- Non-dimmable
- Voltage range 110-265V
- Life to 70% lumen maintenance (L70) - 30,000 hours

## **Product Specs:**

| Input Voltage  | 100~265V AC/DC | Overall Diameter (mm) | 28    |
|----------------|----------------|-----------------------|-------|
| Lamp Base      | G13            | Weight (Kg)           | 0.449 |
| Lifetime Hours | 30000hrs       |                       |       |

## Compliance & Approvals:













This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.