

Product Description: 2W 3 Hour Non-Maintained Emergency Corridor Distribution

Includes LED driver and NiMH battery in a mesh sleeve. Compact downlight fits into a 40mm cut-out. LED module may also be mounted without downlight in a 20mm hole.

SKU Code	Wattage	Colour
AU-EMLD3	2	6000

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Non-maintained LED emergency train with corridor light distribution
- 3 Hour emergency duration
- 2W High power LED
- Includes LED driver and NiMH battery in a mesh sleeve
- Compact downlight fits into a 40mm cut-out
- LED module may also be mounted without downlight in a 20mm hole

Product Specs:

Input Voltage	230~240V	Overall Diameter (mm)	51
Weight (Kg)	0.276	Height (mm)	45
Product Type	Power/Control,Emergency	Cutout Diameter (mm)	40-

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.