

Product Description: 80W IP65 Adjustable Floodlight

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour
AU-FLD802BLK	80	6500	4800	120	Black

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 Mains voltage aluminium LED floodlight
- Ideal for lighting buildings, car parks, plazas, signs, trees, etc.
- Fitted with symmetric reflector
- Equipped with safety glass cover lens with silicon seal
- Powder coated corrosion resistant finish
- All external screws are stainless steel
- Very efficient >70Lm/W
- Comparable to linear halogen: 800W
- Comparable to HID: 200W
- Non-dimmable

Product Specs:

Input Voltage	240~240V AC	IP Rating	IP65
Lifetime L70 (hrs)	30000hrs	Width (mm)	287
Weight (Kg)	5.032	Height (mm)	396

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.