

Product Description: R7 120W IP55 PIR Floodlight

SKU Code	Wattage	Colour	Beam Angle
AU-FLT120BLK	120	3000	60
AU-FLT120W	120	3000	60

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP55 Mains Voltage halogen floodlight with PIR
- Three passive infrared sensors with varying degrees of protection, zones 1 & 3 covering 60°, zone 2 covering 100° with a total detection zone of 220° at 10m
- When movement is detected the motorised floodlight moves to that zone to illuminate the target
- Floodlight remains illuminated for 3 minutes after last movement is detected
- Dusk to dawn override switch to allow operation in daylight
- Indoor speaker warning device sounds alarm when any movement is detected
- Non-dimmable

Product Specs:

Input Voltage	220~250V AC	Lifetime L70 (hrs)	30000hrs
Width (mm)	145	Length (mm)	160
Weight (Kg)	1.324	Projection (mm)	195
Height (mm)	145		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.