

Product Description:

10W IP65 Non-Dimmable Fire Rated Downlight

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-FRL603PC/40	10	4000	500	50	40	Polished Chrome
AU-FRL603SN/40	10	4000	500	50	40	Satin Nickel
AU-FRL603W/40	10	4000	500	50	40	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Integrated LED driver connected to loop-in / loop-out FASTFIX connector (Included)
- Tested in 30, 60 & 90 minute fire rated ceilings
- Life to 70% lumen maintenance (L70) - 40,000 hours
- IP65 high power LED fire rated downlight
- UK Patent Application - 1212923.5
- Tested to BS EN 1365-2:2000
- Non-dimmable
- International Design Registration No. DM/080 178
- IP65 high power LED fire rated downlight

## Product Specs:

Input Voltage	110~240V	IP Rating	IP65
Lifetime L70 (hrs)	75000hrs	Length (mm)	155
Overall Diameter (mm)	88	Weight (Kg)	0.405
Height (mm)	120	Cutout Diameter (mm)	65-72

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.