

Product Description:

m7[™] 7W IP65 Fixed Non-Dimmable Fire Rated Downlight - INSULATION COVER CAP NOT INCLUDED

Fixed, integrated, fire rated 7W LED downlight with driver-on-board and high voltage, single source LED chip. Interchangeable bezels available in White, Matt White, Polished Chrome and Satin Nickel. Fitted with 40° lens. Rated to 30, 60 and 90 minute fire ceilings. Complies with BS EN 1365-2:2000 (fire resistance), BS EN ISO 140-3: 1995 and BS EN ISO 140-6: 1998 (Acoustics), BS EN 13141-1:2400 (Air leakage). Non-Dimmable.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-FRL701/27	7	2700	360	52	40	
AU-FRL701/30	7	3000	400	58	40	
AU-FRL701/40	7	4000	435	63	40	
AU-FRL701MW/30	7	3000	400		40	Matt White
AU-FRL701MW/40	7	4000	435	63	40	Matt White
AU-FRL701PC/30	7	3000	400		40	Polished Chrome
AU-FRL701PC/40	7	4000	435	63	40	Polished Chrome
AU-FRL701SN/30	7	3000	400		40	Satin Nickel
AU-FRL701SN/40	7	4000	435	63	40	Satin Nickel
AU-FRL701W/30	7	3000	400		40	White
AU-FRL701W/40	7	4000	435	63	40	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	40000hrs	Length (mm)	78
Overall Diameter (mm)	78	Weight (Kg)	0.248
Height (mm)	75	Product Type	Downlights, Fire-Rated Downlight
Cutout Diameter (mm)	60-65	Operating Temp. (Max) °C	25°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.