

Product Description:

m10™ 10W IP65 Trimless Dimmable Fire Rated Downlight

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-FRLD814/27	10	2700	420	42	40	White
AU-FRLD814/30	10	3000	450	45	40	White
AU-FRLD814/40	10	4000	500	50	40	White

Line Drawing Polar Curve Colour

Feature & Benefits

- Rated to 30, 60 & 90 minute fire ceilings
- United Kingdom Patent Application No. 1405622.0
- icDOB™ (Driver on Board) for maximum reliability and lifetime NO SEPARATE DRIVER **REQUIRED**
- CrystalCool™ next generation thermal management offers brighter light for longer
- Mains voltage single source HVLED™ chip eliminates overshadowing and offers controlled dimming
- Patented LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- ErP compliant High colour rendering index (Ra) >80
- 40° lens supplied, interchangeable 24° & 60° lenses sold separately

- FastFix[™] rapid install system connector included
- Trimless IP65 rated bezel for a clean flush finish
- BS EN 1365-2:2000 (Fire resistance)
- BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics)
- BS EN 13141-1:2004 (Air leakage)
- 5 Year Warranty see www.auroralighting.com for details
- (L70) at a 40,000 hour lifetime

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	40000hrs
Weight (Kg)	0.330
Cutout Diameter (mm)	90-90

Input Frequency	50/60HZ
IP Rating	IP65
Overall Diameter (mm)	78
Height (mm)	128
Operating Temp. (Max) °C	25°C

Compliance & Approvals:



















Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.