




Product Description: 100W LED IP65 Dimmable Highbay - Installed and Uninstalled


Range of highly efficient 110lm/W LED highbays in 4000K. Available in 100W version. 1-10V dimming function as standard allowing for installations with daylight or occupancy sensors. Fitted with 120° beam angle as standard. Supplied with a 1.5m mains cable. This product was installed and then removed due to a specification error. Products are sold as used but in fact never turned on.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|--------------|---------|--------|--------|-------------|------------|---------------|----------|
| AU-HB100B/40 | 100 | 4000 | 11000 | 110 | 120 | Black | Dimmable |
| AU-HB100B/60 | 100 | 6000 | 10000 | 100 | 120 | Black | Dimmable |

Line Drawing



Polar Curve



Colour

Feature & Benefits

- IP65 rated and die-cast housing for maximum protection in all environments - IK08 impact rating
- High thermal efficient aluminium heatsink - low operating temperature
- 1-10V dimming function built in as standard - allows for use with daylight or occupancy sensors
- Significant energy savings and reduced maintenance over HID highbays
- Ideal for use in warehousing, manufacturing, conference centres, industrial lighting, canopies etc.
- High power factor 0.95
- 120° beam angle as standard
- 1.5kV surge protection

Product Specs:

| | | | |
|--------------------------|-------------|--------------------------|----------|
| Input Voltage | 100~240V AC | Input Frequency | 50/60HZ |
| Power Factor | 0.95 | IP Rating | IP65 |
| Lifetime L70 (hrs) | 50000hrs | IK Rating | IK08 |
| Overall Diameter (mm) | 400 | Weight (Kg) | 6.792 |
| Height (mm) | 220 | Product Type | Highbays |
| Operating Temp. (Min) °C | -20°C | Operating Temp. (Max) °C | 25°C |

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.