



Product Description: m10™ 15W IP65 RGB Fire Rated Downlight

SKU Code	Wattage	Beam Angle
AU-M10RGB	15	40

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Fire rated RGB LED colour changing downlight
- CrystalCool™ next generation thermal management offers brighter light for longer
- Patented LEDchroic™ lens provides anti-glare, precise beam control and even colour mixing
- 3 in 1 RGB LED chip provides even colour mixing and higher colour output
- 3 Channel DMX decoder included
- 12V DC Constant voltage LED driver required (not supplied)
- Can be used with AU-DMXRGBC wall controller or any DMX control system
- Complete RGB colour spectrum including white (the white produced by RGB products is not the same as the white produced by single colour LEDs)
- (L70) at a 40,000 hour lifetime
- 5 Year Warranty – see www.auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	40000hrs	Overall Diameter (mm)	88
Weight (Kg)	0.361	Height (mm)	83
Cutout Diameter (mm)	65-72	Operating Temp. (Max) °C	25°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.