



Product Description: 75-1000VA Remote Dimmer

SKU Code

AU-RMD1000RF

Line Drawing

Polar Curve

Colour

Feature & Benefits

- 1000W Dimmer suitable for the control of dimmable electronic transformers, toroidal transformers, and tungsten lamps WITHOUT de-rating
- Replaceable HRC fuse to allow replacement if damaged by the failure of GZ/GU10 lamps
- Not suitable for use with fluorescent lamps
- Not suitable for LED loads
- Leading edge phase control
- Dimmer module may be mounted in the ceiling void, cupboard etc.
- Dimmer is controlled by momentary switches, therefore there is no buzzing at the switch position
- Hold down switch for dimming control
- Minimum load 75W, maximum load 1000W
- Integrated over-temperature protection fuse
- Smooth dimming operation from 0-100% light output
- Complies with the latest Electrical Safety standard for dimmer switches EN 60669-2-1:2000 & EN 61058-1:1992+A1
- EMC compliance - EN 55015, EN 61000, EN 61547

Product Specs:

Input Voltage	240~240V AC	Width (mm)	45
Length (mm)	145	Weight (Kg)	0.281
Height (mm)	33		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.