

Product Description: Universal™ Adjustable Fire Rated Downlight

The only Fire Rated Downlight that we know of that is suitable for ANY Bulb technology (halogen, CFL, or LED), along with allowing insulation material to be placed on top of the fitting guard. It also comes fitted with a GU10 lampholder .A truly great product which solves all your specification and installation needs in 1 fell swoop.

SKU Code	Finish Colour
AU-UNIF792MW	Matt White
AU-UNIF792PC	Polished Chrome
AU-UNIF792SN	Satin Nickel
AU-UNIF792W	White

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Registered Community Design - 001926429 European Patent - EP1726873B1
- Universal fire rated downlight allows the use of short-form halogen, CFL and LED lamps
- Increased ventilation slots allow heat from all lamp types to be effectively dissipated
- Fitted insulation cover cap allows the downlights to be IC rated - covered with insulation material if necessary. Downlight insulation guard not required
- Tested in 30, 60 & 90 minute fire rated ceilings, 2 Year guarantee
- Reduced recess depth for shallow ceiling voids
- Supplied with GU10 lampholder fitted and optional MR16 lampholder for freedom of lamp choice
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation

## Product Specs:

Input Voltage	~240V AC	Lamp Base	GU10
Width (mm)	135	Overall Diameter (mm)	95
Weight (Kg)	0.341	Height (mm)	132
Cutout Diameter (mm)	85-		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.