

Product Description:

Universal™ IP65 Fixed Fire Rated LED Downlight - Inc Bezel + 500 Lumen LED Lamp

Universal™ range of fixed, adjustable and IP65 rated fire rated downlights optimised for LED lamps. Supplied with GU10 lamp holder and LED Lamp. Interchangeable bezels available in White, Polished Chrome and Satin Nickel. Fitted with insulation cover cap. Rated to 30, 60 and 90 minute fire ceilings. Complies with BS EN 1365-2: 2014 (fire resistance), BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics). Lamp included pick /30 for Warm White and /40 for Cool White

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-UNIF863	50					
AU-UNIF863MW	50					Matt White
AU-UNIF863MW/30	5	3000	500	100	60	Matt White
AU-UNIF863MW/40	5	4000	520	104	60	Matt White
AU-UNIF863PC	50					Polished Chrome
AU-UNIF863PC/30	5	3000	500	100	60	Polished Chrome
AU-UNIF863PC/40	5	4000	520	104	60	Polished Chrome
AU-UNIF863SN	50					Satin Nickel
AU-UNIF863SN/30	5	3000	500	100	60	Satin Nickel
AU-UNIF863SN/40	5	4000	520	104	60	Satin Nickel
AU-UNIF863W	50					White
AU-UNIF863W/30	5	3000	500	100	60	White
AU-UNIF863W/40	5	4000	520	104	60	White

Feature & Benefits

- Universal fire rated downlight allows the use of halogen, CFL and LED lamps
- Increased ventilation slots allow heat from all lamp types to be effectively dissipated
- Fitted insulation cover cap allows the downlights to be IC rated - covered with insulation material if necessary. Downlight insulation guard not required
- Interchangeable twist & lock bezels - Included on Auroraclearance.com
- Supplied with GU10 lampholder fitted
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- BS EN 1365-2: 2014 (fire resistance)
- BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
IP Rating	IP65	Lamp Base	GU10
Width (mm)	125	Overall Diameter (mm)	89
Weight (Kg)	0.245	Product Type	Downlights
Cutout Diameter (mm)	72-		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.