




**Product Description:** Orbital<sup>™</sup> 15W Polycarbonate IP66 Round Bulkhead

The IP66 Orbital<sup>™</sup> bulkhead range is simple yet perfect for bulkhead applications. Engineered with a tough polycarbonate body and opal diffuser for even light output with no LED hot spots, all versions and accessories are impact resistant and designed to last. Available in two wattages, white and black housing, interchangeable eyelid bezels, emergency and microwave options. This range ticks all the boxes for any installation. Life not affected by frequent switching e.g. when used with occupancy controls.


SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-BH15BLK/30	15	3000	1100	74	120	Black	Non Dimmable
EN-BH15BLK/30MS	15	3000	1100	74	120	Black	Microwave
EN-BH15BLK/40	15	4000	1150	77	120	Black	Non Dimmable
EN-BH15BLK/40EM	17	4000	1150	68	120	Black	Emergency
EN-BH15BLK/40EMMS	17	4000	1150	68	120	Black	Emergency Microwave
EN-BH15BLK/40EMR	17	4000	1150		120	Black	Emergency
EN-BH15BLK/40MS	15	4000	1150	77	120	Black	Microwave
EN-BH15BLK/40MSC	15	4000	1150	77	120	Black	Non Dimmable
EN-BH15W/30	15	3000	1100	74	120	White	Non Dimmable
EN-BH15W/30MS	15	3000	1100	74	120	White	Microwave
EN-BH15W/40	15	4000	1150	77	120	White	Non Dimmable
EN-BH15W/40EM	17	4000	1150	68	120	White	Emergency
EN-BH15W/40EMMS	17	4000	1150	68	120	White	Emergency Microwave
EN-BH15W/40EMR	17	4000	1150		120	White	Emergency
EN-BH15W/40MS	15	4000	1150	77	120	White	Microwave
EN-BH15W/40MSC	15	4000	1150	77	120	White	

## Line Drawing



## Polar Curve

## Colour



## Feature & Benefits

- IP66 LED bulkhead not affected by frequent switching
- IK10 rated for maximum vandal resistance
- Rear entry access wiring compartment for easy installation
- Interchangeable eyelid bezel accessory available
- Separate 20mm conduit side entry
- Wall or ceiling mounted - accessories included
- Emergency and microwave options available
- Adjustable light detector from 2-50 lux
- Adjustable hold time 5 seconds to 30 minutes
- 1.5kV surge protection
- For ambient temperatures from -25° C to 40° C
- 5 year warranty

## Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	25000hrs
Lamp Base	None
Weight (Kg)	0.876
Product Type	Bulkheads
Operating Temp. (Max) °C	40°C

Input Frequency	50/60HZ
IP Rating	IP66
IK Rating	IK10
Overall Diameter (mm)	300
Projection (mm)	95
Operating Temp. (Min) °C	-25°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.