



Product Description:

Spryte<sup>™</sup> 8W Fixed Integrated IP40 Dimmable LED Downlight

Spryte<sup>™</sup> LED downlight range is the ideal energy efficient non-fire rated solution for new build or retrofit halogen, R63 and R80 reflector lamp installations. Fitted with the edge-to-edge, multifaceted 60° wide beam EnFiniti<sup>™</sup> lens, these downlights allow for high light output and low glare while still providing a sparkling halogen like optical appearance in a compact sized fitting. Now also available in 8W ball-joint adjustable version alongside the fixed for maximum application flexibility.

| SKU Code     | Wattage | Colour  | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|--------------|---------|---------|--------|-------------|------------|---------------|----------|
| EN-DDL101/27 | 8       | 2700    | 600    | 75          | 90         | White         | Dimmable |
| EN-DDL101/30 | 8       | 3000    | 620    | 78          | 90         | White         |          |
| EN-DDL101/40 | 8       | 4000    | 680    | 85          | 90         | White         |          |
| Line Drawing |         | Polar C | urve   |             | Colour     |               |          |

## Feature & Benefits

- Energy efficient LED Downlight for halogen retrofit applications
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- EnFiniti™ edge-to-edge multifaceted polycarbonate lens creates low glare and halogen like appearance
- 8W supplied with fixed white bezel. 10W supplied with interchangeable round & square white bezels
- 60 degree version IP44 rated. 90 degree version IP40 rated
- Ideal for residential applications
  1.5kV surge protection such as bedrooms, dining rooms and lounge areas
- Pre-wired with 500mm 2 core
- 3 year warranty

## **Product Specs:**

| Input Voltage        | 220~240V AC |
|----------------------|-------------|
| Power Factor         | 0.5         |
| Lifetime L70 (hrs)   | 25000hrs    |
| Weight (Kg)          | 0.105       |
| Cutout Diameter (mm) | 60-60       |

| Input Frequency       | 50/60HZ |
|-----------------------|---------|
| IP Rating             | IP44    |
| Overall Diameter (mm) | 78      |
| Height (mm)           | 53      |

## Compliance & Approvals:

| 1 |
|---|
| ı |
| ı |
| ı |
|   |

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.