AURORA® LIGHTING

Reflector-Fit™




Product Description: Reflector-Fit™ 18W Triac Dimmable Downlight


The Reflector-Fit™ range comes with a high powered COB which can provide up to 122lm/W. Featuring a sparkling multifaceted aluminium reflector designed for exceptional light control and providing a 60 degree beam angle for focused downlighting. Available in four different wattage's.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DDL618/30	18	3000	2110	118	60	White	Triac Dimmable
EN-DDL618/40	18	4000	2200	123	60	White	Triac Dimmable
EN-DDL618DA/40	18	4000	2200	123	60	White	DALI Dimmable
EN-DDL618V/40	18	4000	2200	123	60	White	1-10V Dimmable


Line Drawing



Polar Curve



Colour



White

Feature & Benefits

- Energy efficent COB LED downlights
- 60° beam angle
- Triac dimmable as standard
- Plug and play remote driver for easy installation
- IP44 rated
- 1.5kV surge protection
- SEAI: EN-DDL618/40 - LIG84985
- 5 Year Warranty

Product Specs:

Input Voltage	200~240V AC	Input Frequency	50/HZ
Power Factor	0.9	IP Rating	IP44
Lifetime L70 (hrs)	40000hrs	Overall Diameter (mm)	190
Weight (Kg)	0.981	Height (mm)	75
Product Type	Downlights	Cutout Diameter (mm)	160-170
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	45°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.