





Product Description:

Lumi-Fit[™] 18W High Performance Dimmable Downlight

The range of triac dimmable Lumi-FitTM commercial downlights deliver up to an impressive 106lm/W. Supplied with remote driver and fitted with an acrylic diffuser to reduce glare and for even light distribution. With multiple wattages and sizes on offer this range meets the needs for countless new commercial applications or an upgrade for compact fluorescent fittings in existing applications.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DDLH818/30	18	3000	1600	89	100	White	Triac Dimmable
EN-DDLH818/40	18	4000	1900	106	100	Matt White	Triac Dimmable
EN-DDLH818DA/30	18	3000	1600	89	100	White	DALI Dimmable
EN-DDLH818DA/40	18	4000	1900	106	100	Matt White	DALI Dimmable
EN-DDLH818V/40	18	4000	1900	106	100	Matt White	1-10V Dimmable

Line Drawing	Polar Curve	Colour
		Matt White

Feature & Benefits

- Low cost energy saving compared to compact fluorescents
- Life not affected by frequent switching e.g. when used with occupancy controls
- Triac dimmable as standardPlug and play remote driver for
 - Plug and play remote driver for easy installation
- DALI version available to order

IP54 rated

- 1.5kV surge protection
- 5 year warranty

Product Specs:

Input Voltage	200~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	50000hrs
Lamp Base	None
Weight (Kg)	0.967
Product Type	Downlights
Operating Temp. (Min) °C	-20°C

Input Frequency	50/60HZ
IP Rating	IP54
IK Rating	IK06
Overall Diameter (mm)	228
Height (mm)	45
Cutout Diameter (mm)	200-210
Operating Temp. (Max) °C	45°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.