




Product Description:

Lumi-Fit[™] 25W High Performance Dimmable Downlight


The range of triac dimmable Lumi-Fit[™] commercial downlights deliver up to an impressive 106lm/W. Supplied with remote driver and fitted with an acrylic diffuser to reduce glare and for even light distribution. With multiple wattages and sizes on offer this range meets the needs for countless new commercial applications or an upgrade for compact fluorescent fittings in existing applications.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DDLH825/30	25	3000	2350	94	100	White	Triac Dimmable
EN-DDLH825/35	25	3500	2350	94	100	White	Triac Dimmable
EN-DDLH825/40	25	4000	2600	104	100	Matt White	Triac Dimmable
EN-DDLH825DA/30	25	3000	2250	90	100	White	DALI Dimmable
EN-DDLH825DA/35	25	3500	2350	94	100	White	DALI Dimmable
EN-DDLH825DA/40	25	4000	2600	104	100	Matt White	DALI Dimmable
EN-DDLH825V/30	25	3000	2350	94	100	White	1-10V Dimmable
EN-DDLH825V/40	25	4000	2600	104	100	Matt White	1-10V Dimmable

Line Drawing



Polar Curve



Colour



Matt White

Feature & Benefits

- Low cost energy saving compared to compact fluorescents
- Life not affected by frequent switching e.g. when used with occupancy controls
- Triac dimmable as standard
- Plug and play remote driver for easy installation
- DALI version available to order
- IP54 rated
- 1.5kV surge protection
- 5 year warranty

Product Specs:

Input Voltage	200~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP54
Lifetime L70 (hrs)	50000hrs	IK Rating	IK06
Lamp Base	None	Overall Diameter (mm)	228
Weight (Kg)	1.005	Height (mm)	45
Product Type	Downlights	Cutout Diameter (mm)	200-210
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	45°C

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.