




Product Description: E8[™] Fixed 8W Dimmable Fire Rated Downlight


The E5[™] and established E8[™] fixed and adjustable fire rated downlights set new levels in performance. Featuring the sparkling low glare multifaceted EnFiniti[™] lens and delivering up to 390lm from the 4.5W version and 640lm from the 8W. The E5[™] and E8[™] are packed with features and benefits which allow for a quick and cost effective installation while still providing users with optimum performance and energy saving LED technology.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | SKU Type |
|-----------|---------|--------|--------|-------------|------------|----------------|
| EN-DE8/30 | 8 | 3000 | 580 | 73 | 60 | Triac Dimmable |
| EN-DE8/40 | 8 | 4000 | 620 | 78 | 60 | Triac Dimmable |

Line Drawing



Polar Curve



Colour

Feature & Benefits

- EnFiniti™ edge-to-edge multifaceted polycarbonate lens for low glare and halogen like appearance
- Wide 60° beam angle delivers increased light distribution
- Fibre based insulation coverable - up to 300mm
- Integrated driver with new push fit loop in/out terminals suitable for use with solid or stranded cable for easy installation
- Super slim interchangeable IP65 bezels for fixed version provide a high end sleek finish
- Tested in 30, 60 & 90 min fire rated ceilings
- 3 year warranty

Product Specs:

| | | | |
|--------------------------|----------------------------------|--------------------------|---------|
| Input Voltage | 220~240V AC | Input Frequency | 50/60HZ |
| Power Factor | 0.85 | IP Rating | IP65 |
| Lifetime L70 (hrs) | 25000hrs | IK Rating | IK02 |
| Lamp Base | None | Overall Diameter (mm) | 85 |
| Weight (Kg) | 0.241 | Height (mm) | 87 |
| Product Type | Downlights, Fire-Rated Downlight | Cutout Diameter (mm) | 70-70 |
| Operating Temp. (Min) °C | -20°C | Operating Temp. (Max) °C | 25°C |

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.