




Product Description: CurveE[™] 10W Baffled Dimmable IP44 Downlight


Introducing the stylish CurveE[™] LED downlight range, this low glare downlight has a sleek baffled design with the light source recessed back to reduce glare. Available in matt white these triac dimmable downlights are an ideal non-fire rated solution for hospitality and residential applications in areas where fire rating is not required.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-DLB101D/30	10	3000	920	92	60	White	Triac Dimmable
EN-DLB101D/40	10	4000	970	97	60	White	Triac Dimmable
EN-DLB101DBLK/40	10	4000	970	97	60	Black	Triac Dimmable
EN-DLB101DDA/30	10	3000	920	92	60	White	DALI Dimmable
EN-DLB101DDA/40	10	4000	970	97	60	White	DALI Dimmable
EN-DLB101DV/30	10	3000	920	92	60	White	1-10V Dimmable
EN-DLB101DV/40	10	4000	970	97	60	White	1-10V Dimmable

Line Drawing



Polar Curve



Colour



Matt White

Feature & Benefits

- Baffled design for low glare - LED recessed by 10mm
- Plug and play remote driver for easy installation
- IP44 rated - ideal for hospitality and residential applications such as corridors, living areas, bedrooms, dining rooms and zone 2 of bathrooms
- UGR19 (Unified Glare Rating)
- 1.5kV surge protection
- 5 year warranty
- 3 year onsite warranty (registration required) *Terms and conditions apply

Product Specs:

Input Voltage	220~240V AC	Power Factor	0.90
IP Rating	IP44	Lifetime L70 (hrs)	50000hrs
IK Rating	IK02	Lamp Base	None
Overall Diameter (mm)	80	Weight (Kg)	0.245
Height (mm)	60	Product Type	Downlights
Cutout Diameter (mm)	70-72	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	45°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.