





Product Description:

Helius™ 100W Adjustable IP65 LED Floodlight


The Helius™ range of floodlights are perfect for both residential and commercial IP65 applications. Their slim profile and clean black finish make them as unobtrusive as possible. Available in 10W, 30W, 50W, 100W, 200W and 300W versions with black housing.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FL100A/40	100	4000	7500	75	120	Black	Non Dimmable
EN-FL100A/65	100	6500	7500	75	120	Black	Non Dimmable

Line Drawing

Polar Curve

Colour



Feature & Benefits

- IP65 rated LED floodlight rated with slim design
- Durable high quality paint minimises impact of corrosion
- Tempered glass provides excellent protection
- Die-cast aluminium housing
- Pre-wired with 800mm of cable
- 1.5kV surge protection
- Warning Note: Not suitable for post top mounting
- 3 year warranty

Product Specs:

Input Voltage	110~240V AC		
Power Factor	0.9		
Lifetime L70 (hrs)	25000hrs		
Lamp Base	None		
Weight (Kg)	5.018		
Product Type	Floodlights		
Operating Temp. (Max) °C	35°C		

Input Frequency	50/60HZ	
IP Rating	IP65	
IK Rating	IK08	
Width (mm)	335	
Height (mm)	315	
Operating Temp. (Min) °C	-30°C	

Compliance & Approvals:















Warranty

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.