



## Product Description: Slim-Fit™ 12W IP44 Round Low Profile Downlight

The range of Slim-Fit™ low profile downlights are engineered to deliver superior light output and uniformity utilising the latest edge-lit LED technology. At only 25mm deep including bracket, they are an ideal solution where ceiling voids are limited but high lumen output is required.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-PL12B/30	12	3000	660	55	110	Matt White	Non Dimmable
EN-PL12B/30EM	12	3000	660	55	110	Matt White	Emergency
EN-PL12B/40	12	4000	780	65	110	Matt White	Non Dimmable
EN-PL12B/40EM	12	4000	780	65	110	Matt White	Emergency
EN-PL12B/65	12	6500	850	71	110	Matt White	Non Dimmable
EN-PL12B/65EM	12	6500	850	71	110	Matt White	Emergency
EN-PL12BDA/30	12	3000	660	55	110	Matt White	DALI Dimmable
EN-PL12BDA/40	12	4000	780	65	110	Matt White	DALI Dimmable
EN-PL12BDA/65	12	6500	850	71	110	Matt White	DALI Dimmable
EN-PL12BV/30	12	3000	660	55	110	Matt White	1-10V Dimmable
EN-PL12BV/40	12	4000	780	65	110	Matt White	1-10V Dimmable
EN-PL12BV/65	12	6500	850	71	110	Matt White	1-10V Dimmable

Line Drawing

Polar Curve

Colour

## Feature & Benefits

- Low cost energy savings compared to compact fluorescents
- Edge-lit low profile ideal for installations with limited recess space (25mm) and shallow ceiling voids
- Plug & play remote driver supplied (40mm space required)
- Separate triac dimmable driver available
- Life not affected by frequent switching e.g. when used with occupancy controls
- IP44 rated
- 1.5kV surge protected
- 3 year warranty

## Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP44
Lifetime L70 (hrs)	25000hrs	IK Rating	IK07
Lamp Base	None	Overall Diameter (mm)	174
Weight (Kg)	0.271	Height (mm)	25
Product Type	Downlights	Cutout Diameter (mm)	157-157
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

## Compliance & Approvals:

## Warranty:

---

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.