

Princeton





Product Description:

Princeton™ 1800mm 40W Linear

The PrincetonTM surface mounted LED linear batten offers up to 50% energy savings in comparison to the traditional fluorescent alternative. The high quality polycarbonate diffuser ensures uniform light distribution, eliminating hot spots. Delivering 110lm/W, the batten matches the footprint of traditional fluorescents so is perfect for retrofitting. Fitted with push-fit terminal block for even faster installation.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|----------------|---------|--------|--------|-------------|------------|---------------|----------------|
| EN-SF1840/40 | 40 | 4000 | 4400 | 110 | 110 | White | Non Dimmable |
| EN-SF1840DA/40 | 40 | 4000 | 4400 | 110 | 110 | White | DALI Dimmable |
| EN-SF1840EM/40 | 40 | 4000 | 4400 | 110 | 110 | White | Emergency |
| EN-SF1840V/40 | 40 | 4000 | 4400 | 110 | 110 | White | 1-10V Dimmable |







Feature & Benefits

- Steel housing and high quality polycarbonate diffuser
- Delivering 110lm/W
- IK06 rated impact resistance
- Stand version fitted with pushfit terminals for fast installation
- Multiple BESA mounting points
- 5 Year Warranty
- 3 year onsite warranty (registration required) *Terms and conditions apply

Product Specs:

| Input Voltage | 220~240V AC |
|--------------------------|-------------|
| Power Factor | 0.92 |
| Lifetime L70 (hrs) | 50000hrs |
| Width (mm) | 208 |
| Weight (Kg) | 3.737 |
| Product Type | Linears |
| Operating Temp. (Max) °C | 50°C |

| Input Frequency | 50/60HZ | | |
|--------------------------|---------|--|--|
| IP Rating | IP20 | | |
| IK Rating | IK06 | | |
| Length (mm) | 1788 | | |
| Height (mm) | 70 | | |
| Operating Temp. (Min) °C | -30°C | | |

Compliance & Approvals:











This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.