

Product Description: MR16 Adjustable Chamfered Fire Rated Downlight

SKU Code	Wattage	Finish Colour
A2-DLL932PB	50	Polished Brass
A2-DLL932PC	50	Polished Chrome
A2-DLL932SN	50	Satin Nickel
A2-DLL932SS	50	
A2-DLL932W	50	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Suitable for 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Includes 50W MR16 or GU10 Aluminium reflector lamp (excluding A2-DLM924/A2-DLM963)
- Reduced height fire rated can allows installation in shallow ceiling voids
- 2 Year guarantee

Product Specs:

Input Voltage	12~12V AC
Overall Diameter (mm)	90
Cutout Diameter (mm)	75-

Lamp Base	GU5.3
Weight (Kg)	0.272

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.