



Product Description: GU10 11W Fire Rated Downlight

This 240V GU10 Pressed Steel Fixed 11W Low Energy Fire Rated Downlight has a reduced recess depth for shallow ceiling voids. This downlight is also fitted with intumescent material which completely seals the downlight and cut-out in the event of a fire. Suitable for 30, 60 & 90 minute fire rated ceilings.

SKU Code	Wattage	Finish Colour
A2-DLM924PB	11	
A2-DLM924PC	11	Polished Chrome
A2-DLM924SN	11	Satin Nickel
A2-DLM924SS	11	
A2-DLM924W	11	

Line Drawing

Polar Curve

Colour

Feature & Benefits

- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Reduced height fire rated can allows installation in shallow ceiling voids

Product Specs:

Input Voltage	220~240V AC	Lamp Base	GU10
Overall Diameter (mm)	80	Weight (Kg)	0.214
Cutout Diameter (mm)	60-		

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.