Product Description: GU10 Fixed Fire Rated Downlight

Fixed Spring Clip Fire Rated Downlight. Suitable for Halogen and CFL GU10 lamps.

SKU Code	Finish Colour
A2-DLM941PB	Polished Brass
A2-DLM941PC	Polished Chrome
A2-DLM941SN	Satin Nickel
A2-DLM941SS	Satin Silver
A2-DLM941W	White

Line Drawing



Polar Curve

Colour

Feature & Benefits

- UK Patent GB2426321
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Not for use with dichroic halogen (cool beam) lamps
- Tested in 30, 60 & 90 minute fire rated ceilings
- Tested to BS476 Part 21
- BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- Optional MR16 lampholder (AU-0501F) available for flexibility of lamp choice
- Lamp not included
- Reduced height fire rated can allows installation in shallow ceiling voids
- 3 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC
Lamp Base	GU10
Weight (Kg)	0.256
Cutout Diameter (mm)	65-

Input Frequency	50/60HZ
Overall Diameter (mm)	80
Product Type	Downlights

Compliance & Approvals:

Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.