



Product Description:

Adjustable Downlight

Recessed LED IP20 tilting 30 ° TBT. Equipped with a COB LED 7W up to 700lm and a driver LED 350mA non dimmable. Total consumption 10W. Cast aluminum body. Reflector in high performance faceted aluminum, medium beam 38 °. Passive heatsink with metal fins. White or brushed aluminum finish. Ra> 80. Power factor 0.8. 30 000 hours at L70. 2 years warranty.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AL-13063	10	3000	650	65	38	White
AL-13063AB	10	3000	650	65	38	Brushed Aluminium
AL-13064	10	4000	700	70	38	White
AL-13064AB	10	4000	700	70	38	Brushed Aluminium

Line Drawing Polar Curve Colour

Feature & Benefits

- Spot déco blanc ou alu brossé orientable 30°
- Réflecteur aluminium facetté faisceau 38°. Diffuseur verre clair
- Dissipateur passif avec ailettes en métal
- COB LED 7W jusqu'à 700lm
- Equipé d'un driver LED 350mA
- Consommation totale 10W
- Rendement des couleurs (Ra) >80
- Facteur de puissance 0.8
- Non gradable

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.8
Lifetime L70 (hrs)	30000hrs
Overall Diameter (mm)	90
Product Type	Downlights
Operating Temp. (Max) °C	25°C

	Input Frequency	50/60HZ
_	IP Rating	IP20
	IK Rating	IK05
	Height (mm)	83
	Cutout Diameter (mm)	-75

Compliance & Approvals:











vvarranty

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.