




Product Description: Isored Adjustable 5W GU10 Non Dimmable Recessed Downlight Pack


Ideal for new or renovation projects, the Isored range is designed to guarantee perfect air tightness of ceilings. The unique shape of the can and flexible connection tab ensure easy installation in standard cut-outs even under all types of insulation and without deterioration. Equipped with a quick-release connector that can be used without tools, it is available with a 5W ICE™ LED lamp for maximum energy savings.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AL-13120ABS	5	3000	500	100	38	Satin Nickel
AL-13120S	5	3000	500	100	38	White
AL-13121ABS	5	4000	520	104	38	Satin Nickel
AL-13121S	5	4000	520	104	38	White

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Recessed airtight LED downlight - Building regulation compliant
- Suitable for all types of insulation materials (fibre / blown / sprayed) and vapour barrier tarpaulin
- Aluminium +/-20° adjustable bezel for an elegant finish
- Supplied with a quick-release and plug-in terminals connector
- Flexible connection bracket for easy installation
- Pack supplied with 5W ICE™ GU10 lamp
- White & satin nickel finish options
- 2 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.5	IP Rating	IP20
Lifetime L70 (hrs)	25000hrs	Lamp Base	GU10
Length (mm)	130	Overall Diameter (mm)	86
Weight (Kg)	0.245	Height (mm)	98
Product Type	Downlights	Cutout Diameter (mm)	75-75

Compliance & Approvals:



Warranty:

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.