



Product Description:

Esofit Plus 9W 4" Retrofit Trim - Wet Location

Designed to service the needs of the residential/commercial market, the Aurora Esofit Plus retrofit 4" & 5-6" trims are ideal for replacing existing incandescent, fluorescent and halogen lights with their superior high powered low wattage LEDs with CRI>90 for true color rendering. Available in fixed versions with a recessed baffle or adjustable with gimbal feature allowing 355° rotation. The Esofit Plus installs easily into most standard 4" or 5-6" recessed CANs, including IC and NON-IC housings, for both retrofit and new construction. These trims use only 9, 13 or 18 Watts of power & produce 600, 800 and 1200 lumens. Compatible with most line voltage dimmers.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|--------------|---------|--------|--------|-------------|------------|---------------|
| AR-DL3340/27 | 9 | 2700 | 600 | 67 | 90 | White |
| AR-DL3340/30 | 9 | 3000 | 600 | 67 | 90 | White |
| AR-DL3340/40 | 9 | 4000 | 600 | 67 | 90 | White |
| AR-DL3340/50 | 9 | 5000 | 600 | 67 | 90 | White |

| Line Drawing | Polar Curve | Colour | |
|--------------------|-------------|--------|--|
| | | | |
| Feature & Benefits | | | |
| Product Specs: | | | |
| | | | |

| Input Voltage | 120~120V AC |
|--------------------------|-------------|
| Power Factor | 0.9 |
| Lifetime L70 (hrs) | 50000hrs |
| Width (mm) | 135 |
| Height (mm) | 71 |
| Cutout Diameter (mm) | 100-110 |
| Operating Temp. (Max) °C | 40°C |

| Input Frequency | 60/60HZ |
|--------------------------|--------------|
| IP Rating | Wet Location |
| Lamp Base | E26 |
| Overall Diameter (mm) | 135 |
| Product Type | Downlights |
| Operating Temp. (Min) °C | -20°C |

Compliance & Approvals:

Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.