AURORA®
LIGHTING





## Product Description: 44W Adjustable Horizontal Floodlight

Our range of architectural floodlights add visual interest and security to office parks and other exteriors while using less energy and requiring minimal upkeep. Our small, 44W LED floodlights are available in 33, 45 and 25 x 58 degree beam spreads. They come in two colors, blue and white; the white has a neutral 4200K color temperature and an output of 2200 lumens. Perfect for smaller spaces, our small LED floodlights efficiently accent and enhance exteriors, including building facades, displays and signs. In commercial and residential applications, these powerful floodlights can highlight the beauty of the natural environment well past daylight hours, in addition to providing added safety.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Finish Colour |
|---|---|---|---|---|---|
| AR-FLD25ABK/BL | 44 | | 850 | 20 | Black |
| AR-FLD25ABK/W | 44 | 4200 | 2200 | 50 | Black |
| AR-FLD25ABR/BL | 44 | | 850 | 20 | Bronze |
| AR-FLD25ABR/W | 44 | 4200 | 2200 | 50 | Bronze |
| AR-FLD25AMW/BL | 44 | | 850 | 20 | Matt White |
| AR-FLD25AMW/W | 44 | 4200 | 2200 | 50 | Matt White |
| AR-FLD25ASV/BL | 44 | | 850 | 20 | Matt Silver |
| AR-FLD25ASV/W | 44 | 4200 | 2200 | 50 | Matt Silver |

## Line Drawing




## Polar Curve

## Colour

## Feature & Benefits

- High power aluminum LED floodlight
- Ideal for lighting buildings, parking lots, plazas, signs, trees, etc.
- Suitable for wet locations / IP65
- Equipped with safety glass cover lens with silicon seal
- Highly efficient heat dissipation design
- Mounting bracket may be adjusted 90° in both directions
- Powder coated corrosion resistant finish
- All external screws are stainless steel
- Non-dimmable
- 5 Year warranty
- Suitable for wet locations

## Product Specs:

| | | | |
|---|---|---|---|
| Input Voltage | 120~277V | Input Frequency | 50/60HZ |
| Power Factor | 0.75 | IP Rating | IP65 |
| Lifetime L70 (hrs) | 40000hrs | Width (mm) | 70 |
| Length (mm) | 220 | Height (mm) | 310 |
| Operating Temp. (Min) °C | -20°C | Operating Temp. (Max) °C | 60°C |

## Compliance & Approvals:

## Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.