



Product Description: 33W Garage Light


Increase the security and visibility of commercial areas, parking lots, and garages with Aurora's range of commercial LEDs. This range has the lifetime, durability and an assortment of shapes, light output and beam angles for a variety of applications and local code compliance. Our square, outdoor LED canopy luminaire has a bronze powder coat finish, die cast housing, an efficacy of 76 lm/W and a neutral 4000K color temperature. Suitable for wet, outdoor locations, our LED canopy luminaires are ceiling mount only.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle
AR-GL132	33	4000	2525	77	110

Line Drawing

Polar Curve

Colour



Feature & Benefits

- LED fixture for parking lot, general area and security lighting
- Optic system with prismatic pattern
- Die cast housing
- Can be installed on junction boxes or direct wall mounted with feed through conduit access
- Bronze powder coated corrosion resistant finish
- Suitable for wet locations / IP44
- Ceiling mount only
- 5 Year warranty
- Suitable for damp locations

Product Specs:

Input Voltage	100~277V AC	Input Frequency	50/60HZ
IP Rating	IP44	Lifetime L70 (hrs)	50000hrs
Width (mm)	315	Length (mm)	315
Projection (mm)	241	Height (mm)	241
Product Type	Bulkheads	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	60°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.