




## Product Description: Versitile™ 36W 1' x 4' 0-10V Dimmable Up/Down Panel


The new Versitile suspended edge-lit LED light panels with 60% down and 40% upward light distribution offer a fantastic architectural solution offering a subtle uplight offering all round lighting solutions. Fitted with high transmission diffuser for minimal glare. A chunky and robust white frame with a 0-10V Driver and suspension box provided as standard.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AR-LPUD1436/35	36	3500	3780	105	120	RAL9016
AR-LPUD1436/40	36	4000	3780	105	120	RAL9016
AR-LPUD1436/50	36	5000	3780	105	120	RAL9016

## Line Drawing



## Polar Curve



## Colour

## Feature & Benefits

- A range of high energy-efficiency edge-lit LED flat panels for office and commercial lighting applications
- Suspension kit supplied as standard with the panel
- PMMA light guide and PS diffuser, for even light 60% functional light and 40% uplighting to create overall feeling of space and light
- White profile frame – depth just 1.18"
- Adjustable length of suspension allowing a drop of around 47" as standard and positioning of suspension wire along the length of the panel allows for minor adjustments
- CRI>80
- High power factor - 0.90
- Aurora's dimmable panels provide a simple 0-10V solution that is compatible with stand alone 0-10V dimmers as well as larger lighting control systems and allows for installation with daylight or occupancy sensors
- Compatible with Lutron 0-10V Dimmers
- Operating temperature -4°F to 104°F
- Suitable for damp locations
- Available color temperatures 3500K, 4000K, 5000K
- DLC (DesignLights Consortium®) certified
- (L70) at 50,000 hour lifetime
- 5 Year warranty

## Product Specs:

Input Voltage	100~277V AC	Input Frequency	60/60HZ
Power Factor	0.90	IP Rating	Damp Location
Lifetime L70 (hrs)	50000hrs	Width (mm)	295
Length (mm)	1195	Weight (Kg)	3.35
Height (mm)	23	Product Type	Panels
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.