

Product Description: 1200mm IP65 Twin Anti-Corrosive

Range of single and twin polycarbonate LED non-corrosive luminaires fitted with vandal resistant polycarbonate body and diffuser. For ease of installation, the diffuser is permanently attached with two clips and the gear tray is fitted with restraints. Fitting is supplied with mounting brackets for ceiling and wall mounting or suspension. Anti-tamper stainless steel clips are supplied with the luminaire. Multiple drill-out conduit entry points are fitted at the back and ends of the housing. Replacement gear trays available.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-ANT1204A/40	50	4000	4100	82	120	Grey	Non Dimmable
AU-ANT1204A/40D	50	4000	4100	82	120	Grey	Dimmable
AU-ANT1204A/40DALI	50	4000	4100	82	120	Grey	DALI Dimmable
AU-ANT1204A/40EM	50	4000	4100	82	120	Grey	Emergency
AU-ANT1204A/40MS	50	4000	4100	82	120	Grey	Microwave
AU-ANT1204A/40MSEM	50	4000	4100	82	120	Grey	Emergency Microwave
AU-ANT1204A/60	50	6000	4180	84	120	Grey	Non Dimmable
AU-ANT1204A/60D	50	6000	4180		120	Grey	Dimmable
AU-ANT1204A/60DALI	50	6000	4180	84	120	Grey	DALI Dimmable
AU-ANT1204A/60EM	50	6000	4180	84	120	Grey	Emergency
AU-ANT1204A/60MS	50	6000	4180	84	120	Grey	Microwave
AU-ANT1204A/60MSEM	50	6000	4180	84	120	Grey	Emergency Microwave
AU-ANT1204A/65	50	6500	5000	100	120	Grey	Non Dimmable

Feature & Benefits

- IP65 vandal resistant polycarbonate body and diffuser - ideal for carparks and food preparation areas
- Diffuser permanently attached by two clips for ease of installation
- Gear tray restraints for ease of installation and maintenance
- Optional mounting brackets (included) allow for ceiling, wall or suspended mounting
- Anti-tamper stainless steel clips supplied as standard
- Multiple drill-out conduit entry points at the back and ends of housing
- IK08 impact rating
- Replacement gear trays available - contact sales office for details
- Emergency, Microwave and DALI options available
- Microwave sensor detection range up to 12 meters.
- Adjustable detection range, hold time and lux level settings
- (L70) at a 25,000 hour lifetime
- 3 Year Warranty – see www.auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.95	IP Rating	IP65
Lifetime L70 (hrs)	25000hrs	IK Rating	IK08
Width (mm)	140	Length (mm)	1274
Weight (Kg)	1.825	Height (mm)	90
Operating Temp. (Max) °C	25°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.