



Product Description: T8 2 x 20W IP65 Non-Corrosive Fluorescent

SKU Code	Wattage
AU-ANT220LED	40

Line Drawing

Polar Curve

Colour

Feature & Benefits

- IP65 Mains voltage T8 LED polycarbonate non-corrosive fitting
- Includes T8 4000K LED lamp
- Control gear not required
- Suitable for car parks, sports stadia, boiler rooms, factories, farm buildings etc.
- Impact resistant polycarbonate body and opal diffuser
- Supplied with lockable tamper proof diffuser clips
- 20mm conduit entries
- Not suitable for Fluorescent T8 tubes
- Non-dimmable
- *Add suffix EM to catalogue number for Emergency option, maintained, 3 hour duration

Product Specs:

Input Voltage	220~250V AC	IP Rating	IP65
Lifetime L70 (hrs)	30000hrs	Width (mm)	160
Length (mm)	1270	Weight (Kg)	3.156
Height (mm)	160		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.