

Product Description:

10W IP44 Fixed Dimmable Downlight with FastFix Connector

Integrated 10W LED downlight with driver-on-board and high voltage, single source LED chip. Fitted with CrystalCool™ thermal management. LEDchroic™ lens for radiant light quality and precise beam definition. Available in 2700K, 3000K and 4000K. Dimmable option available. Fitted with 40° lens and white bezel.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-CD101AKW/30	10	3000	550	55	40	White
AU-CD101AKW/40	10	4000	600	60	40	White

Line Drawing Polar Curve Colour

Feature & Benefits

- icDOB™ (Driver on Board) for maximum reliability and lifetime
 NO SEPARATE DRIVER REQUIRED
- CrystalcoolTM next generation thermal management offers brighter light for longer
- Mains voltage single source HVLEDTM chip eliminates overshadowing and offers controlled dimming
- Patented LEDchroic[™] lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- ErP compliant High colour rendering index (RA) >80
- Compact profile for low recessed ceilings
- 1.5M Flex And Plug Fitted
- BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics)
- BS EN 13141-1:2004 (Air leakage)
- Life to 70% lumen maintenance (L70) at a 40,000 hour lifetime

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.8
Lifetime L70 (hrs)	40000hrs
Overall Diameter (mm)	75
Cutout Diameter (mm)	60-65

Input Frequency	50/50HZ
IP Rating	IP44
Length (mm)	75
Height (mm)	75

Compliance & Approvals:













Warranty

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.