

Product Description: 4.9W Adjustable Dimmable Downlight

Integrated Adjustable 5W LED downlight with driver-on-board and high voltage, single source LED chip. Fitted with CrystalCool™ thermal management. LEDchroic™ lens for radiant light quality and precise beam definition. Available in 2700K, 3000K and 4000K. Dimmable option available. Fitted with 40° lens and white bezel..

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-CD52AKW/30	5	3000	310	62	40	White
AU-CD52AKW/40	5	4000	325	65	40	White

Line Drawing

Polar Curve

Colour

Feature & Benefits

- icDOB™ (Driver on Board) for maximum reliability and lifetime - NO SEPARATE DRIVER REQUIRED
- Crystalcool™ next generation thermal management offers brighter light for longer
- Mains voltage single source HVLED™ chip eliminates overshadowing and offers controlled dimming
- Patented LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- Compact profile for low recessed ceilings
- (L70) at a 40,000 hour lifetime
- 1.5M Flex And Plug Fitted

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/50HZ
Power Factor	0.75	IP Rating	IP20
Lifetime L70 (hrs)	40000hrs	Length (mm)	98
Weight (Kg)	0.245	Height (mm)	51
Cutout Diameter (mm)	85-		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.