Product Description: PL-C (4-Pin) 2 x 13W CFL Downlight

SKU Code	Wattage	Finish Colour
AU-CFD132	26	Black
AU-CFD132EM	26	

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Compact fluorescent downlight with faceted aluminium reflector
- For use with long life horizontally mounted compact fluorescent lamps for high efficiency and reduced running costs
- Suitable for display lighting in shops, offices, showrooms, hotels, etc.
- Easily installed by means of a 3-point fixing system
- Low height of fitting allows for installation in shallow ceiling voids
- Tiltable lampholders for ease of lamp replacement
- Single & twin lamp versions from 10W to 13W
- Lamps are not included
- Supplied with non-dimmable high frequency electronic ballast with European key components as standard
- Screwless loop-in, loop-out primary wiring terminals
- Dimmable version is 1-10V and requires additional wiring
- Accessories include twist and lock bezels, IP65 splash proof lens and floating glasses
- Maximum ceiling thickness - 20mm
- Non-dimmable
- *Add suffix EM to catalogue number for Emergency option

Product Specs:

Input Voltage	220~240V AC	Overall Diameter (mm)	200
Weight (Kg)	0.977	Cutout Diameter (mm)	175-

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.