

Product Description: PL-C (4-Pin) 1 x 18W CFL Downlight

SKU Code	Wattage	Finish Colour
AU-CFD181	18	Black
AU-CFD181DALI	18	Black
AU-CFD181DALIEM	18	Black
AU-CFD181DM	18	Black
AU-CFD181DMEM	18	Black
AU-CFD181EM	18	Black

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Compact fluorescent downlight with faceted aluminium reflector
- For use with long life horizontally mounted compact fluorescent lamps for high efficiency and reduced running costs
- Suitable for display lighting in shops, offices, showrooms, hotels, etc.
- Easily installed by means of a 3-point fixing system
- Low height of fitting allows for installation in shallow ceiling voids
- Tiltable lampholders for ease of lamp replacement
- Single & twin lamp versions from 18W to 42W. Lamps are not included
- Supplied with non-dimmable high frequency electronic ballast as standard
- Screwless loop-in, loop-out primary wiring terminals
- Dimmable version is 1-10V and requires additional wiring
- Accessories include twist and lock bezels, IP65 splash proof lens and floating glasses
- Maximum ceiling thickness - 20mm
- Dimmable option available
- *Add suffix DM to catalogue number for Dimmable Electronic Ballast
- *Add suffix EM to catalogue number for Emergency option
- *Add suffix DMEM to catalogue number for Dimmable Emergency option
- *Add suffix DALI for DALI option
- *Add suffix DALIEM for DALI Emergency option

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Length (mm)	505	Overall Diameter (mm)	255
Weight (Kg)	1.127	Height (mm)	140
Cutout Diameter (mm)	233-		

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.