

Product Description: dSeries™ 12W IP44 Dimmable Downlight

Range of dSeries™ fixed, dimmable IP44 LED downlights featuring CrystalCool™ thermal management. External driver included. Smooth and linear dimming on most leading and trailing edge dimmers. Available in 12W, 18W and 29W. Suitable for cut-out of 90mm, 150mm and 210mm. Available in 3000K and 4000K. DALI, Emergency and Baffled versions available. Supplied with White bezel.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-DL10013AW/30	12	3000	850	71	95	White	Dimmable
AU-DL10013AW/30D	12	3000	850	71		White	DALI Dimmable
AU-DL10013AW/30EM	12	3000	850			White	Emergency
AU-DL10013AW/40	12	4000	910	76		White	Dimmable
AU-DL10013AW/40D	12	4000	910	76		White	DALI Dimmable
AU-DL10013AW/40EM	12	4000	910			White	Emergency
AU-DLB10013AW/30	12	3000	850	71	80	White	Dimmable
AU-DLB10013AW/30D	12	3000	850		80	White	DALI Dimmable
AU-DLB10013AW/40	12	4000	910		80	White	Dimmable
AU-DLB10013AW/40D	12	4000	910		80	White	DALI Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- International Design Registration No. DM/080 178
- Latest version is IP44
- Patented CrystalCool™ Technology
- Reduced heatsink due to CrystalCool™ Technology allows installation in shallow ceiling voids
- Lightweight polycarbonate bezel
- Downlight supplied with remote triac dimmable LED driver
- Smooth and linear dimming on most leading / trailing edge dimmers
- Life to 70% lumen maintenance (L70) - 40,000 hours
- 5 Year Warranty - see www.auroralighting.com for details

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP44
Lifetime L70 (hrs)	40000hrs	Overall Diameter (mm)	116
Weight (Kg)	0.331	Height (mm)	53
Product Type	Downlights	Cutout Diameter (mm)	90-
Operating Temp. (Max) °C	25°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.