

Product Description:

18W Low Profile Downlight

24V Transformer Required Please source Separately (Not Included)

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
AU-DL10218SS/30	18	3000	1000	56	120	Satin Silver
AU-DL10218SS/40	18	4000	1100	62	120	Satin Silver
AU-DL10218W/30	18	3000	1000	56	120	
AU-DL10218W/40	18	4000	1100	62	120	

Line Drawing Polar Curve Colour

Feature & Benefits

- 40mm low profile edge-lit LED downlight suitable for use in limited recess space
- 24V Transformer Required Please source Separately (Not Included)
- Life to 70% lumen maintenance3 Year guarantee40,000 hours

Side-lit with SMD LEDs

Product Specs:

Input Voltage	24~24V DC
Power Factor	0.9
Lifetime L70 (hrs)	35000hrs
Weight (Kg)	0.545
Cutout Diameter (mm)	185-

Input Frequency	50/60HZ	
IP Rating	IP44	
Overall Diameter (mm)	200	
Height (mm)	40	

Compliance & Approvals:











This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.